

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 184 083 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
06.03.2002 Bulletin 2002/10

(51) Int Cl.7: **B05B 7/00, B05B 12/12,
B05B 12/00, B05B 17/06**

(21) Application number: **00118715.2**

(22) Date of filing: **30.08.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Hess, Joseph**
2022 Bevaix (CH)
• **Körner, Joachim**
88690 Uhldingen (DE)

(71) Applicant: **Ing. Erich Pfeiffer GmbH**
78315 Radolfzell (DE)

(74) Representative: **Balsters, Robert et al**
Novagraaf SA 25, Avenue du Pailly
1220 Les Avanchets - Geneva (CH)

(54) **Smart miniature fragrance dispensing device for multiple ambient scenting applications and environments**

(57) The smart fragrance dispensing device (1) comprises an airless fragrance reservoir (1a) containing a principal medium (8), a flow channel (3) for receiving said principal medium (8), a liquid spray dispenser (2) connected to said reservoir (1a) for dispensing said principal medium (8) as a spray into said flow channel (3), a programmable driving circuit (5) for operating said liquid spray device so as to create said spray consisting of monodispersive droplets, a memory device (4) carrying and communicating identification information about at least said principal medium (8), its dispensing and diffusing characteristics, said liquid spray dispenser (2) and said reservoir (1a), and a programmable control and communication micro-controller unit (7) linked to said reservoir (1a), said programmable driver circuit (5), and said flow channel (3), and controlling the programmable driver circuit (5) and the flow channel (3) in such a manner that flow is started in time before the driver circuit (5) is activated and stopped in time after the driver circuit (5) is activated and otherwise as a function of information read from said memory device (4), said information being used to adapt to the individual perception of a user by means of adjusting to a desired level and memorising said level.




FIG. 2

BEST AVAILABLE COPY

Description

[0001] The present invention concerns a smart fragrance-dispensing device having an electronic control module for allowing dispensing of a specific fragrance as a spray in reply to an electronic command.

[0002] The document EP-A-0 714 709 already describes a smart fragrance dispenser. This device is arranged for the simultaneous spraying of several stored scents.

[0003] The spraying device has two or more cartridges of different capacities, which are fitted to the spray device. The spray device projects their contents from heads supported on a rigid cylindrical tube containing electric wires from a battery and an annular power electronic circuit concentric with the longitudinal axis. Drops of controlled size from one or both cartridges are projected on demand from several ducts under programmed control which is activated e.g. by a proximity detector. Waste is prevented by a safety system switching the device between a standby state and a state of readiness.

[0004] However, with such a device, although the amount of ejected fragrance may be controlled, this amount merely depends on the amount programmed to be expelled. If such a device is used to control, e.g. ambient air in a specific surrounding, such as a room or a theatre, there is no way of telling if such amount will suffice or not to control the ambient air. Furthermore, if several different fragrances are to be expelled sequentially from the device, there is a large risk of contamination of a second fragrance by a first as no means are provided for ensuring a full evacuation of the first fragrance without any residue being left in the spray means.

[0005] The present invention has as its aim to overcome the above-mentioned problems. Furthermore, the present invention aims to provide a smart fragrance dispensing device capable of precisely controlling the expelled fragrance in view of its user's requirements and/or in view of the location in which the device is being used.

[0006] Thus, the present invention concerns a smart fragrance-dispensing device as defined in the appended claims.

[0007] Thanks to the smart fragrance-dispensing device of the present invention, it is possible to adapt the expelled fragrance to the individual perception of the user by means of adjusting to a desired level and memorising this level.

[0008] Furthermore, the present invention also allows controlling the ambient atmosphere of the environment in which the user of the device is present.

[0009] Other features and advantages of the smart fragrance-dispensing device according to the present invention will become clear from reading the following description, which is given solely by way of a non-limitative example thereby referring to the attached drawings in which:

FIGURE 1A is a schematic view of a preferred embodiment of the smart fragrance-dispensing device according to the present invention,

FIGURE 1B shows an exploded view of the device of figure 1a.

FIGURE 2 shows a detailed view of the device of Figure 1, and

FIGURE 3 shows a schematic diagram of a driver circuit for driving the present smart fragrance-dispensing device.

[0010] As shown in figure 1, the smart fragrance-dispensing device 1 according to the present invention may be formed in a compact manner. The device shown is a handheld battery-operated device. Smart miniature fragrance dispensing device 1 consists of an exterior housing 11 for accommodating the different components constituting the device. A frame 13 is further provided which may contain a power source, such as two batteries 12 for powering the device. Of course, the power supply may be any other suitable low-power source, such as a car power supply, solar supply or the like. Housing 11 comprises a containment space for at least one airless fragrance reservoir 1a. Preferably, this reservoir 1a has an active or passive delivery system and contains a principle fragrance medium, referenced 8 (see Figure 2). Advantageously, built into or otherwise arranged within the containment space of reservoir 1a, a compensating reservoir, not shown, may be provided for containing a compensation medium which gradually fills the part of which has become free of reservoir 1a due to expelling of principle medium 8. Such a reservoir and its complementary compensating reservoir are already known as such, and are described, e.g., in the document US-A-6 062 430, which is incorporated herewith by reference. In short, the reservoir, in fact, contains a first and a second volume respectively filled with a first medium, in the present case the principle medium, and a second medium, wherein the first and second volumes are operationally variable. Preferably, this reservoir is encapsulated to avoid contamination, evaporation, atmospheric influences (UV etc.) of the principle medium and allows to operate the device without adding any preservatives, stabilisers etc. to the principle medium, as also explained in the above-mentioned US-A-6 062 430. Of course, other airless reservoirs such as capillary tubes or aluminium bags may be used.

[0011] Reservoir 1a is provided with a liquid spray dispenser 2 (see figure 2) for dispensing principle medium 8 into a flow channel 3 which is arranged, for instance, within the top part of housing 11 to receive the principle medium as a spray of droplets. Preferably, flow channel 3 is a controllable induced mixed media flow channel for mixing principle medium 8 dispensed from reservoir 1a with an ambient medium, such as a gas, contained within the flow channel, as will be explained in more detail further on. The flow channel expels the mixed media through an outlet provided in housing 11 so as to allow

the fragrance to enter the environment.

[0012] Housing 11 further contains electronic circuitry suitably arranged for driving liquid spray dispenser 2 and for controlling flow channel 3, and activation means 14 for activating the electronic circuitry and for expelling the fragrance. Such activation means may be for example a simple push button provided on the top of housing 11.

[0013] Preferably, airless fragrance reservoir 1a is assembled in a leak-tight manner to spray dispenser 2.

[0014] Reference will now further be made to figure 2. The above-mentioned electronic circuitry contained within smart fragrance dispensing device 1 further comprises at least one memory or other electronic device 4 carrying and communicating identification information about at least principle medium 8 itself, for instance a fragrance, its dispensing and diffusing characteristics, and about the smart fragrance dispensing device 1 and/or its reservoir 1a.

[0015] Flow channel 3 may consist of a plastic part as represented in figure 2 in which heaters may be provided in the form of flow inducing elements 3a providing controlled flows of the sprayed principle medium 8 for dispersion into the induced flow of the ambient medium as largely monodispersive droplets of a range of approximately from about 1 to 10 μm , but preferably smaller than 10 μm in diameter. Flow inducing elements 3a may be in the form of tungsten rings which are individually and sequentially electrically connected in order to create a controlled "chimney effect", i.e. a directed flow of the ambient medium through the flow channel before, during and after the principle medium 8 is dispensed therein, for carrying the mixed media outwards in an efficient manner. In fact, it is possible to regulate the activation of the Tungsten rings by applying different currents to the rings so as to control the intensity of the rings thus creating a temperature gradient due to the fact that different rings will heat more or less quickly. Further, the time of applying the current may also be varied. The controlled combination of temperature gradient and actuation time regulates the passage of the principle medium into the gaseous phase and with that the controlled dispersion of the fragrance as a function of its properties, such as its volatility, its dispersion ratio, its intensity and the like, into the surrounding environment or room. Thus, this controlled "chimney effect" allows for a control of the absence or presence of the fragrance.

[0016] Of course, instead of heating elements, a fan could be used to create such a "chimney effect", although a fanless, thermal convection solution is preferred.

[0017] Preferably, heating elements 3a also stay on for a given time after the dispensing in order to ensure that the flow carries out all the remnants of the sprayed fragrance. This is especially important when several fragrances are expelled sequentially so as to avoid mutual contamination.

[0018] Liquid spray dispenser 2 is arranged for expel-

ling the principle medium 8 through a non-vibrating membrane substrate having non-vibrating, straight output channels, and which extracts the principle medium directly in a valve-less configuration from airless fragrance reservoir 1a. Preferably, dispenser 2 is constituted by a liquid droplet spray device according to European patent application publication number EP-A-0 923957. Thus, spray dispenser 2 comprises a housing formed by a top-substrate and a bottom-substrate with a space there between for receiving principle medium 8. Ultrasonic vibrating means are arranged on the bottom substrate for vibrating such and for thus forcing the liquid medium through straight outlet channels and nozzles provided in the non-vibrating top substrate so as to expel a spray of monodispersive droplets, as explained in detail in the above-mentioned European application. Dispenser 2 may further be provided with a protection against fragrance evaporation, and is positioned top or bottom up or in any suitable position in space in conjunction with the controllable induced mixed media flow channel 3.

[0019] The electronic circuitry within the inventive dispensing device 1 further comprises at least one programmable, miniaturised very low energy ultrasonic driver circuit 5 for driving in a valve-less configuration the smart fragrance dispensing device 1 in conjunction with the ultrasonic spray dispenser 2 and providing sensor-less information on the full/empty state of fragrance dispensing device 1.

[0020] Figure 3 shows in more detail the diagram of ultrasonic driver circuit 5. Driver circuit 5 comprises a piezoelectric driving circuit containing a transistor, not shown, for exciting piezoelectric element 5c, which thus constitutes the ultrasonic vibrating means of liquid spray dispenser 2, so as to cause the latter to vibrate. Such driving circuits are well known as such and will thus not be described in detail here. A driver programmable switch 5b is further provided to allow control of the driving circuit. Switch 5b is connected to a micro-controller forming part of the electronic circuitry, as will be explained in detail further on.

[0021] Referring back to figure 2, preferably, at least one multi-sensor unit 6 is further provided. Each unit may be a separated module that can be operatively linked to smart fragrance-dispensing device 1, and is preferably temperature compensated and may be battery or mains powered. Multi-sensor unit 6 consists of at least one ambient air flow sensor and at least one calibrated ambient medium characteristics sensor or sensor-array, for sensing the ambient air motion and condition as compared to a pre-calibrated reference level and the absence or presence and the increase or decrease of the concentration of the principle medium in the ambient medium, e.g. the air of a room. Thus, by detecting a variation in the air condition or motion, it is thus possible to release the fragrance in a controlled manner.

[0022] A non-disposable control and communication

micro-controller unit 7 is further provided for controlling the smart fragrance dispensing device 1, the multi-sensor unit 6, the ultrasonic driver circuit 5, as mentioned above this driver is micro-controlled, and the mixed media flow channel 3. Control and communication unit 7 may be of the wired or wireless type and it controls ultrasonic driver circuit 5 and mixed media flow channel 3 in such a manner that the induced mixed media flow is started in time before the driver circuit is activated and stopped in time after the driver circuit is deactivated and otherwise in function of information read from memory device 4, this information being used to adapt to the individual perception of a user by means of adjusting to a desired level and memorising said level.

[0023] As can be seen in figure 2, control and communication unit 7 and multi-sensor unit 6 are linked in a wireless manner. To this effect, control and communication unit 7 and multi-sensor unit 6 are each provided with a wireless transceiver, respectively referenced 7a and 6a allowing for the wireless communication.

[0024] Control and communication unit 7 controls and commands the dispensing from smart fragrance dispensing unit 1 via the programmable, ultrasonic driver circuit(s) 5 and mixed media flow channel 3 in accordance with rule-based instructions and information derived from the dispensing characteristics contained in and read from memory device 4 and further in accordance with information read from multi-sensor unit 6 and calculations performed based on the desired presence or absence of single or multiple principle media or components in the ambient medium, (the calculations being performed as simple rule, fuzzy logic rule, neural network or virtual sensor quantification rule processing).

[0025] The desired concentration level(s) of single or multiple principle media in the ambient medium, their sequence of dispensing, their time of presence or absence in the ambient medium and their rate of diffusion, their availability, their concentration as read by multi-sensor unit 6 are adjustable either directly in control and communication unit 7 or remotely via an interface 9 built-in control and communication unit 7. This remote control may be carried out, e.g. by telephone, PC, Net appliance etc or Internet communication line or wireless communication, Bluetooth™, and the like, and according to the applicable communication protocols for such devices, web-appliances etc. However, this interface may of course also be voice-controlled.

[0026] Interface 9 is provided with communication means 9a which are suitably arranged on the software and/or hardware level to communicate with audio/video synchronising, sequencing, time lead or lag with regards to video or audio and depending on the properties of the fragrance, e.g. its volatility or dispersion ratio etc., thereby controlling instructions for example on movie projectors. For example, in the MPEG standard, subtitles are triggered using a signal just before the frame requiring the subtitle appears. This trigger signal, or a similar signal, may be used for audio synchronising and for the

control of the time lag or time lead. The time lag/lead may be varied as a function of the properties of the fragrance. Indeed, as may be understood, if a fragrance dispenses quickly into the surrounding air, the release command may be triggered later than if the dispensing ratio is slow.

[0027] In analogy, communication unit 7 is compatible with the applicable multi-media, hypermedia and AV protocols such that interface 9 may be used for the dispensing of single or multiple fragrances, of their time of presence or absence in the ambient air, information about their availability, their rate of diffusion and their concentration as read by the non-disposable multi-sensor unit(s), all of which can be controlled, synchronised by or sequenced with information contained in the respective multimedia support and storage system.

[0028] Thus, the innovation of the present smart fragrance dispensing unit lies principally in the use in multimedia application which results from the miniature and smart concept which allows interfacing with the various multimedia standards mentioned and incorporation into a variety of media from cinema seats to PlayStations™, PC's, Net-appliances or point-of-sale terminals. Thus, the fragrance dispenser with the multi-sensor unit constitutes a "system" that allows this flexibility, exchangeability of cartridges and adaptability to environments and liquids to be dispensed.

[0029] In a further embodiment, control and communication unit 7 is suitably equipped and compatible with the applicable multimedia, hypermedia, Digital Video Broadcasting (DVB) as well as interactive AV protocols, codes and interpreters according to the relevant JPEG, MPEG and MHEG standards, as expressed in the corresponding ISO/IEC documents or according to other proprietary standards or methods in video processing like USB protocol layers (e.g. chapter 8) or QuickTime™ encoding and audio processing (e.g. MIDI, or Dolby™ digital, LPCM, MP3, AAC (Advanced Audio Coding) etc) or as used in video games and other proprietary audio, video, AV and computer graphics techniques and devices.

[0030] This interface 9 is being used for orchestrating the dispensing of single or multiple fragrances, of their time of presence or absence in the ambient air, information about their availability, their rate of diffusion and their concentration as read by the multi-sensor unit(s) 6, all of which can be controlled, synchronised by or sequenced with moving picture, animation, video or audio content, objects etc as contained in the respective multimedia support and storage systems like DVD's and others and related devices, including broadcasting, set-top-boxes, interactive retrieval, VoD (Video on Demand) etc and as can be used in various public or private electronic media environments. Thus, it is further possible to trigger the dispensing of scents to accompany an AV message content.

[0031] In fact, such use of scents may be applied to certain private and public multimedia applications, such

as cinemas, home multimedia centres, multimedia viewing and interactive installations and centres, home-shopping, interactive advertising, advertising on point-of-sale or information etc, where the scents are used to accentuate, expand or complement or other accompany the AV message content. The multi-sensor unit(s) are then located directly in or in close vicinity of the enclosure housing 11 of liquid spray dispenser 2, the ultrasonic driver circuit 5 and the control and communication unit 7 and is connected in a wired or wireless way and where the control and communication unit (7) can be addressed remotely via telephone, or Internet or wireless communication, Bluetooth™ or other.

[0032] Multi-sensor unit 6 may further comprise a presence sensor, referenced 6b, for applications in public environments, e.g. in cinemas, buses, aeroplanes, public washrooms etc, where the smart fragrance dispensing device is arranged in close vicinity of a consumer, e.g. by building it into the back of the seat or the front panel, to detect the presence of the consumer so as to initiate or block the functioning of the smart fragrance dispensing device.

[0033] Housing 11 of smart fragrance dispensing device 1 preferably consists of at least one non-disposable cartridge 10 into which reservoir 1a is fitted. This cartridge may be provided with suitable thermal insulation 10a, an electronically controlled Pelletier element or elements 10b and a temperature sensor 10c, which are controlled by the control and communication unit 7 to maintain reservoir 1a at ambient temperature to avoid evaporation of its content.

[0034] In an advantageous arrangement, control and communication unit 7 is arranged to control the air-conditioning system of an environment in which said housing is arranged before or as a user enters it.

[0035] Multi-sensor unit 6 may be used to detect a certain concentration of a certain, first medium, e.g. cigarette smoke, in the second, ambient medium of the environment in which the device is placed and to release a third medium, e.g. a fragrance, to cover the effect of the first medium by releasing a calculated amount of the third medium.

[0036] Advantageously, for certain private and public places of usage for the present smart fragrance dispensing device, the reservoir 1a is constituted by a different airless system, for example a multilayer polymer/aluminium/polymer bag containing the principle medium 8 and into which at least one spray dispensing device 2 is assembled leak-tight and connected to the other units.

[0037] The principle media contained within reservoir 1a may be a fragrance, insect repellent, air disinfectant, air humidification, (aromatic) essence, food or other flavour replicating liquids and volatiles to be dispensed in order to obtain the desired characteristic of the ambient medium of the room or environment in which the present inventive device is placed for operation.

[0038] In a further advantageous embodiment, smart fragrance dispensing device 1 serves to dispense a par-

amedical substance and comprises a specific sensor for adjustment of the dispensed volume, timing incl. biorhythm and circadian rhythm and concentration of such substance.

[0039] As may be understood from the above, the present invention allows for a miniaturised, very simple, very cost effective device can grow into a smart system by modular expansion of its units. Further, thanks to the cost-effective multi-sensor, ambient characteristics may be detected for user perception controlled dispensing.

[0040] Advantageously, liquid spray dispenser 2 may be operated in such a way that by using a wrong frequency, i.e. not the exact resonance frequency of the piezoelectric vibration means, the dispenser will heat up during a short period of time in order to evacuate the fragrance from the internal volume. The internal volume of the liquid spray dispenser 2 needs to be minimal, preferably from less than 1 µl to several µl.

[0041] Preferably, multi-sensor unit 6 is composed of at least one ambient air flow sensor and at least one calibrated ambient medium characteristics sensor or sensorarray, and uses information from the airflow (direction, flow rate, vectors) which can be combined with information from the sensor array and the memory device 4 related to the characteristics of the principle medium 8 to conclude on the emission of the principle medium fragrance needed to maintain a desired level of fragrance in a given environment, the air renewal rate, the volatilisation of the principle medium etc.

[0042] As such, it is possible for the user to adapt the dispensed fragrance to the individual perception of the user by means of adjusting to a desired level and memorising said level.

[0043] The sensor array can be of the metal oxide, semiconductor (solid state), conducting polymer or electronic nose type. Important is the notion of « calibrated ambient medium characteristics sensor ambient medium being "synthetic air" versus any ambient air detected at a given moment anywhere and the ambient air resulting from the emission of the principle medium into that ambient air. Calibrated also means that the electronics which processes the information from the sensor array « knows » e.g. has been pre-calibrated to at least one « signature or the fingerprint » of a particular principle medium or a variety of such media.

[0044] Preferably, the multi-sensor unit should be operated at a temperature that is sufficiently high (usually more than 400 and less than 600 °C for a semiconductor sensor) in order to avoid condensation and influence of humidity in the air. It should also be operated to control drift.

[0045] Having described a preferred embodiment of this invention, it will now be apparent to one of skill in the art that other embodiments incorporating its concept may be used. It is felt, therefore, that this invention should not be limited to the disclosed embodiment, but rather should be limited only by the scope of the appended claims.

Claims

1. Smart fragrance dispensing device (1) having a housing (11) and comprising:

- a power supply (12),
- an airless fragrance reservoir (1a) containing a principal medium (8),
- a flow channel (3) for receiving said principal medium (8),
- a liquid spray dispenser (2) connected to said reservoir (1a) for dispensing said principal medium (8) as a spray into said flow channel (3),
- a programmable driver circuit (5) for operating said liquid spray device so as to create said spray consisting of monodispersive droplets,
- a memory device (4) carrying and communicating identification information about at least said principal medium (8), its dispensing and diffusing characteristics, said liquid spray dispenser (2) and said reservoir (1a),
- a programmable control and communication micro-controller unit (7) at least linked to said reservoir (1a), said programmable driver circuit (5), and said flow channel (3); said control and communication unit (7) being of the wired or wireless type and controlling said programmable driver circuit (5) and said flow channel (3) in such a manner that the flow is started in time before the driver circuit (5) is activated and stopped in time after the driver circuit (5) is activated and otherwise as a function of information read from said memory device (4), said information being used to adapt to the individual perception of a user by means of adjusting to a desired level and memorising said level.

2. Smart fragrance dispensing device (1) according to claim 1, wherein said flow channel (3) is a mixed media flow channel having an ambient medium therein, and wherein said programmable control and communication micro-controller unit (7) is further also linked to the mixed media flow channel in such a manner that the mixed media flow is started in time before the driver circuit (5) is activated and is stopped in time after the driver circuit (5) is activated and otherwise in function of the information read from said memory device (4).

3. Smart fragrance dispensing device (1) according to claim 1 or 2, further comprising at least one multi-sensor unit (6) provided as a removable module and operatively linked to the smart fragrance dispensing device (1) and consisting of at least one ambient air flow sensor and at least one ambient medium characteristics sensor, said multi-sensor unit (6) sensing the ambient air motion and condition, as compared to a pre-calibrated level, as well as the absence or

presence and the variation of the concentration of said principal medium (8) in said ambient medium, wherein said programmable control and communication micro-controller unit (7) is further also linked to the multi-sensor unit (6)

4. Smart fragrance dispensing device (1) according to claim 3, wherein said control and communication unit (7) further comprises an interface (9) and controls and commands the dispensing from said reservoir (1a) via said programmable driver circuit (5) and said controllable mixed media flow channel (3) in accordance with rule-based instructions and information derived from said dispensing characteristics contained in and read from said memory device (4) and further in accordance with information read from said multi-sensor unit(s) (6) and calculations performed based on the desired presence or absence of single or multiple principle media (8) or components in the ambient medium, the desired concentration level(s) of said single or multiple principle media in the ambient medium, their sequence of dispensing, their time of presence or absence in the ambient medium and their rate of diffusion, their availability, their concentration as read by said non-disposable multi-sensor unit(s) being adjustable either directly in the non-disposable control and communication unit (7) or remotely via said built-in interface (9).

5. Smart fragrance dispensing device (1) according to claim 4, wherein said interface (9) is a voice-controlled interface.

6. Smart fragrance dispensing device (1) according to claim 4, wherein said interface comprises communication means (9a) which are suitably arranged on the software and/or hardware level to communicate with multimedia systems such that said interface (9) is used for the dispensing of single or multiple fragrances, of their time of presence or absence in the ambient air, information about their availability, their rate of diffusion and their concentration as read by said multi-sensor unit(6), all of which being controlled, synchronised by or sequenced with information contained in the respective multimedia system.

7. Smart fragrance dispensing device (1) according to claim 3, wherein said multi-sensor unit further comprises a proximity detector for detecting the presence of a person in the same environment as in which said smart fragrance dispensing device is located so as to control its operation.

8. Smart fragrance dispensing device (1) according to claim 6, wherein said interface (9) receives control commands from said multimedia system for triggering the dispensing of a fragrance as a function of

the output of said multimedia system.

9. Smart fragrance dispensing device (1) according to claim 1, wherein said housing (11) comprises a temperature sensor (10c) and thermal control means (10a, 10b) arranged to maintain said reservoir (1a) at ambient temperature. 5
10. Smart fragrance dispensing device (1) according to claim 1, wherein said principal medium (8) is a fragrance, an insect repellent, an air disinfectant, an air humidification, an essence, or a food or other flavour replicating liquids and volatiles. 10

15

20

25

30

35

40

45

50

55




Figure 1a




Figure 1b




FIG. 2




FIG. 3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 8715

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A,D	EP 0 923 957 A (MICROFLOW ENG SA) 23 June 1999 (1999-06-23) * column 5, line 39 - line 50 * * column 6, line 5 - line 23 * * column 7, line 41 - column 8, line 10 * * column 8, line 46 - column 9, line 21; figures *	1	B05B7/00 B05B12/12 B05B12/00 B05B17/06
A,D	EP 0 714 709 A (MILLET CYRIL ; MILLET JEAN CLAUDE (FR)) 5 June 1996 (1996-06-05) * column 2, line 54 - column 3, line 47 * * column 5, line 29 - line 32 * * column 6, line 5 - line 23; figures *	1	
A	EP 0 878 307 A (HEWLETT PACKARD CO) 18 November 1998 (1998-11-18) * abstract; figure 1 *	1	
A	EP 0 831 384 A (RICOH KK) 25 March 1998 (1998-03-25) * column 8 * * column 9, line 56 - column 10, line 19 *	1	
A	US 5 591 409 A (WATKINS CARL J) 7 January 1997 (1997-01-07) * column 4, line 12 - line 52; figures 1,4 *	1	
A	FR 2 776 947 A (PARFUM INDIGO) 8 October 1999 (1999-10-08) * page 10 - page 11 *	1	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 2 February 2001	Examiner Brévier, F
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 11 8715

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02-02-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0923957	A	23-06-1999	NONE		
EP 0714709	A	05-06-1996	FR	2727329 A	31-05-1996
			DE	69517490 D	20-07-2000
			DE	69517490 T	26-10-2000
EP 0878307	A	18-11-1998	JP	10323995 A	08-12-1998
EP 0831384	A	25-03-1998	JP	10146385 A	02-06-1998
			DE	69700398 D	16-09-1999
			DE	69700398 T	13-01-2000
			ES	2137751 T	16-12-1999
US 5591409	A	07-01-1997	NONE		
FR 2776947	A	08-10-1999	AU	3040499 A	25-10-1999
			EP	1066118 A	10-01-2001
			WO	9951358 A	14-10-1999

EP 00 11 8715

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)